

MURAL SECAMANOS

MURAL HAND DRYER

REF: 306601 / 306603

SERIE: COMPLEMENTOS-SECAMANOS / COMPLEMENTS-HAND DRYERS

DIMENSIONES / MEASUREMENTS: 695 X 295 X 225 mm.

PESO / WEIGHT: 11 kg

CAJA INDIVIDUAL / SINGLE CARTON: 285 X 720 X 360 mm

PESO CON CAJA INDIVIDUAL / SINGLE CARTON WEIGHT: 11,6 Kg

CAJA MASTER / MASTER CARTON: -

CANTIDAD / AMOUNT: -

PESO CAJA MASTER / MASTER CARTON WEIGHT: SCP* / AQP*

*Según cantidades paletizado / According quantities palletized



ACABADO / FINISHED: Blanco y Satinado / White and Satin

DESCRIPCIÓN / DESCRIPTION:

- Fabricado en ABS antibacteriano
- Acabado color blanco
- Motor sin escobillas
- Secamanos mural de alta velocidad 1850 W
- Sistema de detección de manos por lector en la parte inferior
- Sensor superior con detector de salida de manos para corte de funcionamiento
- Iluminación por led durante el funcionamiento de secado
- Con bandeja extraíble recoge-aguas con filtro de partículas
- Equipado con interruptor de encendido-apagado aislado en el lateral
- Con interruptor selector de la velocidad de aire
- Con interruptor para el corte de la resistencia calorífica que consigue un ahorro energético
- Potencia total: 1850 W
- Potencia calorífica: 1000W
- Alimentación: 230 V y 50 Hz
- Caudal de soplado: 89-124 m3/h
- Velocidad del aire: 90-100 m/s
- Temperatura del aire: 35-40 ° C
- Tiempo de secado: 3-6 s
- Consumo: 7.5 A
- Nivel de ruido: 72 db
- Aislamiento eléctrico: Clase I
- Índice de protección: IPX4
- Velocidad del motor: 21000 rpm

- Made of antibacterial ABS.
- White color finish.
- Brushless motor.
- Mural hand dryer of high speed 1850 W.
- Electronic infrared detection sensor when putting hands in the lower part.
- Automatic disconnection system after removing the hands.
- Led light indication when hand dryer is working.
- Removable reservoir of water with particulate filter.
- With isolated on/off switch button in the lateral.
- With a switch to select air speed.
- switch for cutting the heating resistance so that there is more energy saving.
- Total power: 1850 W.
- Heating power: 1000W.
- 230 V and 50 Hz
- Blowing flow: 89-124 m3/h.
- Air speed: 90-100 m/s.
- Air temperatura: 35-40 ° C.
- Dry time: 3-6 s
- Consumption: 7.5 A.
- Level of noise: 72 db.
- Electrical insulation: Class I.
- Waterproof: IPX4.
- Motor speed: 21000 rpm.

CERTIFICACIONES / CERTIFICATIONS:

GS-CE-ROHS.

GS-CE-ROHS standards.

MURAL SECAMANOS

MURAL HAND DRYER

